

- 1. THE UNIQUE IDENTIFICATION CODE OF THE PRODUCT TYPE:** 11/Bib/CSE
- 2. INTENDED USE OR USES:** Dry pressed ceramic tiles and decorations with low water absorption $0,5\% \leq E_b < 3\%$; BI_b Group, unglazed (UGL)/glazed (GL); for laying on floors and/or walls indoors and/or outdoors.
- 3. MANUFACTURER:** CERSANIT S.A.; AL. Solidarności 36; 25-323 Kielce
- 4. SYSTEM(S) OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE:** SYSTEM 4
- 5. HARMONIZED STANDARD:** EN 14411:2012
- 6. DECLARED PERFORMANCE:**

ESSENTIAL CHARACTERISTICS	PERFORMANCE (LEVEL AND/OR CLASS)
Reaction-to-fire performance	A1 _{FL} Classified Without Testing (CWT)
Breaking strength:	
- thickness $\geq 7,5\text{mm}$	$\geq 1100\text{ N}$
- thickness $< 7,5\text{mm}$	$\geq 700\text{ N}$
Bond strength/adhesion [N/mm²]:	
- cementitious adhesives	$\geq 0,5\text{ N/mm}^2$
- dispersion adhesives	$\geq 1\text{ N/mm}^2$
- reaction resin adhesives	$\geq 2\text{ N/mm}^2$
Thermal shock resistance	Meets
Durability for:	
- internal use:	Meets
- external use: resistance to freeze-thaw cycles	Meets
Tactility	NPD - No Performance Determined

A copy of the Declaration of Performance is available on the website: www.cersanit.com; www.opoczno.eu

The performance of the above product is in accordance with the Declaration of Performance. This declaration of performance shall be issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer referred to above.

Place, date:
Kielce, 01.10.2018

Signed on behalf of the manufacturer

QUALITY SYSTEM MANAGER

Jolanta Grzebna