

DECLARATION OF PERFORMANCE NO 02CE/Bla/CSE/04

1. The unique identification code of the product type: **02/Bla/UGL/CSE**

2. Intended use or use:

Dry-pressed ceramic tiles with low water absorption $E_b \leq 0,5\%$; Annex G; Bla group, unglazed (UGL), polished Gres Porcellanato; for interior walls and floors and exterior walls of buildings - as described on the packaging.

3. Manufacturer: **CERSANIT S.A.; AL. Solidarności 36; 25-323 Kielce**

4. System(s) of assessment and verification of constancy of performance: **SYSTEM 4**

5. Harmonised standard: **EN 14411:2012**

6. Declared performance:

| Essential characteristics | Performance (level and/or class) | Harmonised technical specification |
|---|---|---|
| Reaction-to-fire performance | A1 _{FL} | Classified Without Testing (CWT) EN 14411:2012 |
| Release of dangerous substances: | | |
| - Cadmium | Max 0,07mg/dm ² | |
| - Lead | Max 0,8mg/dm ² | |
| Breaking strength: | | |
| - thickness ≥7,5mm | ≥ 1300N | |
| - thickness <7,5mm | ≥ 700N | |
| Bond strength/adhesion [N/mm²]: | | |
| - cementitious adhesives | NPD - No Performance Determined | |
| - dispersion adhesives | | |
| - reaction resin adhesives | | |
| - mortar | | |
| Slippage according to CEN/TS 16165:2012, Annex B | NPD - No Performance Determined | |
| Thermal shock resistance | Meets | |
| Durability for: | | |
| - internal use: | Meets | |
| - external use: resistance to freeze-thaw cycles | Meets | |
| Tactility | NPD - No Performance Determined | |

A copy of the Declaration of Performance is available on the website: www.cersanit.com

The performance of the above product is in accordance with the Declaration of Performance. This declaration of performance shall be issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer referred to above.

Signed on behalf of the manufacturer:

QUALITY SYSTEM MANAGER



Jolanta Grzebna

Kielce, 01.06.2017
(place and date of issue)

.....
(signature)